

- LEGEND**
- PUBLIC ROAD FIXTURE
 - PARKING LOT LIGHT
 - PEDESTRIAN LIGHT
 - BOLLARD
 - CANOPY LIGHT
 - PHASE 2 LIGHT FIXTURES
 - 1.00 CONTOUR LEVEL (fc)
 - 0.50 CONTOUR LEVEL (fc)
 - 0.20 CONTOUR LEVEL (fc)

GENERAL LIGHTING NOTES:

- LIGHTING CALCULATIONS INCLUDE FUTURE LIGHT FIXTURES (* PHASE 2 FIXTURES) IN ORDER TO MEET IESNA STANDARDS FOR THE FUTURE BUILD-OUT. FUTURE LIGHT FIXTURES WOULD NOT BE INSTALLED AS PART OF PHASE 1 AND ARE NOT LISTED IN THE LUMINARIE SCHEDULE.
- MOUNTING HEIGHT EQUATES BETWEEN THE LIGHT SOURCE AND THE GROUND PLANES FOR USING CALCULATION PHOTOMETRIC ANALYSIS. CUT POLES AS NEEDED
- VOLTAGE TO BE VERIFIED BY ELECTRICAL ENGINEER PRIOR TO ORDERING
- DRIVE CURRENT - REVIEW DRIVE CURRENT AND WATTAGE WITH ELECTRICAL ENGINEER AND CONTRACTOR BEFORE INSTALLATION
- DIMMING TO BE VERIFIED BY ELECTRICAL ENGINEER PRIOR TO INSTALLATION. THE FIXTURE SHOULD BE SET AT THE PERCENTAGE (1/3 THE TOTAL POWER) AS SHOWN ON THE LIGHT SCHEDULE.
- BASE MOUNT - SEE LIGHTING PLANS FOR THE FIXTURE'S ORIENTATION.
- SEE LIGHTING PLANS AND DETAILS WITH SPECIFICATIONS FOR LIGHT FIXTURES, POLES, ARMS AND OTHER INFORMATION.

PLAN
REVISED
06/17/2022

